

Large Venue Projector

Vivitek DH3331

Feature Rich 1080p 3D Multimedia Installation Projector



Features

- FullHD 1080p resolution, 5,000 ANSI lumens and a 10,000:1 contrast ratio for the ultimate image quality
- DLP® and BrilliantColor™ technologies from Texas Instruments
- Centered lens for easy setup and installation
- Horizontal and vertical lens shift for greater installation convenience and flexibility
- Distorted and trapezoid image issues are easily corrected with keystone, and 4-corner controls
- HDBaseT™ interface with support for distribution of HD video and digital audio content over standard CAT5e/6 LAN cable
- Broad video connectivity options including: HDMI, VGA-In, DVI-D, Component (5 BNC) (RGBHV), S-Video, Composite Video, VGA-Out
- MHL device compatibility for streaming of video and audio content from a compatible mobile device
- 3D sync port for compatibility with IR (infrared) 3D passive synchronization protocol
- Project 3D content from DLP® Link™, PC based 3D and Blu-ray HDMI
- 12V trigger port for direct communications and automated control of such devices as screens and curtains
- 14W of total 3D audio surround sound power (7W x 2) with multiple audio-in and audio-out ports
- Network ready for integration and system administration via RJ45
- Dual infrared sensors for handy remote control from either in front or behind the projector
- Anti-theft security features include: Kensington® security slot, and security bar

Photos



Specifications

Display Type	Single 0.65" DLP Technology by TI
Brightness	5,000 ANSI Lumens
Native Resolution	1080p (1920 x 1080p)
Maximum Resolution	WUXGA (1920x1200) @60Hz
Contrast Ratio	10,000:1
Lamp Life/Type	1,500/3,500 hours (Normal/Eco Mode) 370W/280W
Throw Ratio	1.25 - 2.13:1
Image Size (Diagonal)	21.2" - 361.4"
Projection Distance	1 - 10m (3.28ft - 32.8ft)
Projection Lens	F=2.45 - 3.22, f= 18.8mm - 32mm
Zoom Ratio	1.7x
Aspect Ratio	16:9
Offset	135.9% / 118%
Keystone Correction	Vertical ±30°, Horizontal ±25°
Horizontal Frequency	15, 31 – 91.4kHz
Vertical Scan Rate	24 - 30Hz, 47 - 120Hz
3D Functionality	Yes (Supports DLP® Link™, IR, Blu-ray 3D)
Speakers	3D Audio Surround Sound (7W x 2)
Lens Shift Range	Vertical: -13.5%, +28.7%
	Horizontal: +/-10.3%
Computer Compatibility	GA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA@60Hz, Mac
Video Compatibility	SDTV (480i, 576i)/EDTV (480p, 576p)/HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
I/O Connection Ports	HDMI v1.4, MHL/HDMI v1.4, VGA-In (x2), DVI-D, Component (5 BNC) (RGBHV), S-Video, Composite Video, Audio-In RCA (L/R), Audio-In (Mini-Jack)(x3), Microphone-In (Mini-Jack), Wired Remote-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), Audio-Out RCA (L/R), 12v Screen Trigger (Mini-Jack), 3D Sync-Out, RS-232, USB Type A Power (5V/2.0A), Wired Remote-Out (Mini-Jack), USB Type B (Service), RJ45, HDBaseT™
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar
Dimensions (W x D x H)	445 x 330.2 x 160.2mm (17.5"x 12.9" x 6.3")
Weight	8.4kg (18.5lbs)
Noise Level	36dB/30dB (Normal/Eco Mode)
Available Color	Dual Tone Color: White and Gray
Power Supply	AC 100-240V, 50/60Hz
Power Consumption	480W (Normal Mode), 380W (Eco. Mode), <0.5W (Standby Mode), <6W (LAN Standby Mode)
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Filter, Documentation Kit
Optional Accessories	Replacement Lamp, HDBaseT™ Transmitter Box

©2015 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.

